Part Number	I20003 -- MN02X4W1-36PT68-3TL6A0A10-S Upgradeable, Power Unit Level Monitoring
Power Configuration	30A, 208V, 4.9kW
Physical Configuration	72 in / 1829 mm Vertical
Description	The I20003 -- MN02X4W1-36PT68-3TL6A0A10-S upgradeable power monitoring PDU delivers comprehensive view of power usage in a data center with Geist's Interchangeable Monitoring Device (IMD). The modular design of the PDU allows the "hot-swappable" IMD to be upgraded as new technology is developed. With its current IMD, the I20003 -- MN02X4W1-36PT68-3TL6A0A10-S offers on-board and web power monitoring display options with quick access to the unit's current, volts, real power, apparent power, power factor and kilowatt hours. By monitoring these critical variables, data center managers can evaluate energy usage trends and ensure maximum uptime. Racknet Enabled - The I20003 -- MN02X4W1-36PT68-3TL6A0A10-S easily integrates with Racknet – Geist's DCiM software. Racknet (purchased separately) collects and reports critical power and environmental data for multiple PDUs in one, user configurable interface. Users gain immediate remote access to trends, alarms and histories of devices in the data center through a standard Web browser. Racknet saves both time and cost associated with managing each device individually. Contact your Geist rep for more details.
Product Summary	I20003 -- MN02X4W1-36PT68-3TL6A0A10-S - Upgradeable, Power Unit Level Monitoring, 30A, 208V, Vertical, (30) Locking IEC C13,(6) Locking IEC C19, breakered, 10 ft power cord with L6-30P, Power – Remote + Current - Local, , Aggregate - Total Unit Monitoring (A, V, W, VA, kWh, PF) Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 1% Accuracy Class Requirements, Circuit/Breaker Monitoring (A) Circuit/Breaker Current Measurements Independently Tested and Verified at 2% Accuracy
Monitoring	Power – Remote + Current - Local
Plug Form	L6-30P
Receptacle	Locking IEC C13 (Quantity: 30) Locking IEC C19 (Quantity: 6)

I20003 -- MN02X4W1-36PT68-3TL6A0A10-S - Product Specification and Options

Monitoring	Power – Remote + Current - Local
Monitoring Level 1	Aggregate - Total Unit Monitoring (A, V, W, VA, kWh, PF) Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 1% Accuracy Class Requirements
Monitoring Level 2	Circuit/Breaker Monitoring (A) Circuit/Breaker Current Measurements Independently Tested and Verified at 2% Accuracy
Quantity Of Inputs	1
Voltage	208V
Current	30A
VA per Input (Load Capacity)	4.9kW
Frequency	50/60 Hz
Over Current Protection	(2) 20A Double Pole Magnetic Breakers
Switch	Breaker/Switch Combination
Scrolling / Rotatable Digital Display	Yes
Power Cable Wire Gauge	10/3
Power Cable Length	10ft
Power Entry Location	Bottom Front
Plug Type	NEMA L6-30P Twistlock
Combined Total Receptacle/Socket Quantity	36
Receptacle/Socket Type #1	Locking IEC C13
Quantity on Face #1	30
Quantity per Breaker #1	15
Style #1	Individual
Voltage per Receptacle/Socket #1	208V
Receptacle/Socket Type #2	Locking IEC C19
Quantity on Face #2	6
Quantity per Breaker #2	3
Style #2	Individual
Voltage per Receptacle/Socket #2	208V
Internal RMS Voltage Sensor	Yes
Internal RMS Current Sensor	Yes
Network Connection	Dual 10/100Mbps Ethernet
Network Protocols Supported and Data Access Formats	HTTP, HTTPS (SSL/TLS), SMTP, SMTPS (SSL), ICMP, DHCP, IPv4, IPv6, Syslog, SNMP v1/v2c/v3, JSON, RSTP
IP Reset Button	Yes
Hard Reboot Button	Yes
Heavy Steel -Black Powder Coat	Yes
Configuration	72in / 1832mm Vertical Rackmount
7938 Vertical Mounting Bracket Kit	Yes
Toolless Mounting Hardware - Center to Center Spacing	61.25in and 64.75in
Made in the USA	Yes
Product Warranty	Five Year
Certification/Agency Approvals	FCC Part 15 Class A Conformance
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	UL & c-UL Listed 60950

Chassis Dimensions (LxWxD)	72in x 2in x 2in
Shipped Weight	16lbs (7.26kg)

Geist Americas

1821 Yolande Ave
Lincoln, NE 68521 USA
1.800.432.3219 or
1.402.474.3400
www.geistglobal.com

Geist Europe

Unit 1, The Monarch Centre,
Venture Way,
Priorswood, Taunton,
Somerset, TA2 8DE UK
+44 (0) 1823 275100
www.geisteurope.com

Geist Asia

China
Tiley Plaza Bldg. A, Unit #2808,
No. 199 Haide 3 Road,
Nanshan Shenzhen,
Guangdong Province, China.
Postal Code: 518000
Tel: +86.755.86639505
www.geistglobal.com

Geist Asia

Hong Kong
Tel: +852 90361927

Email: salesasia@geistglobal.com